


GENUS 5




acciaio

spessore (mm)	peso (Kg/m ²)	Jxx (cm ⁴ /m)	Wxx (cm ³ /m)
0,50	4,65	10,69	11,68
0,60	5,60	12,65	13,81
0,80	7,45	16,42	17,81
1,00	9,31	19,95	21,55



spessore (mm)	interasse cm								
	80	100	120	140	160	180	200	220	240
0,50	570	361	247	181	138	109	86	-	-
0,60	770	489	337	247	185	147	109	81	-
0,80	1515	964	670	451	299	204	147	109	81
1,00	1867	1192	822	546	361	252	181	133	100




spessore (mm)	interasse cm								
	80	100	120	140	160	180	200	220	240
0,50	605	438	334	265	213	179	150	127	109
0,60	772	559	426	334	271	225	190	161	138
0,80	1117	806	611	484	392	323	271	230	196
1,00	1480	1066	806	634	513	426	357	305	242

alluminio

spessore (mm)	peso (Kg/m ²)	Jxx (cm ⁴ /m)	Wxx (cm ³ /m)
0,50	1,59	10,69	11,68
0,60	1,91	12,65	13,81
0,80	2,54	16,42	17,81
1,00	3,18	19,95	21,55



spessore (mm)	interasse cm								
	80	100	120	140	160	180	200	220	240
0,50	444	259	150	95	65	-	-	-	-
0,60	554	314	180	115	75	50	-	-	-
0,80	778	419	239	150	100	70	50	-	-
1,00	1008	519	299	184	124	85	60	-	-



spessore (mm)	interasse cm								
	80	100	120	140	160	180	200	220	240
0,50	378	282	206	161	121	85	60	-	-
0,60	484	348	262	202	146	101	76	56	-
0,80	690	499	373	293	197	136	101	71	56
1,00	918	656	494	363	242	166	121	91	65

Nota: freccia
max = f ≤ l/150.