


UNI PARETE
FISSAGGIO A VISTA



Contattare ufficio tecnico per conformità ai requisiti CAM



acciaio

lato superiore
acciaio 0,4 mm

lato inferiore
acciaio 0,4 mm

| SP | peso | Distanza tra gli appoggi | | | | | U trasmissione |
|-----|-------|--------------------------|------|------|------|------|-------------------|
| | | 1,50 | 2,00 | 2,50 | 3,00 | 3,50 | |
| 25 | 7,79 | 101 | 54 | - | - | - | 0,98 |
| 30 | 7,97 | 129 | 75 | 44 | - | - | 0,77 |
| 40 | 8,19 | 145 | 115 | 75 | 47 | - | 0,58 |
| 50 | 8,57 | 185 | 150 | 109 | 72 | 48 | 0,46 |
| 60 | 9,11 | 207 | 146 | 99 | 68 | 48 | 0,38 |
| 80 | 9,71 | 305 | 245 | 190 | 140 | 105 | 0,29 |
| 100 | 10,47 | 385 | 305 | 240 | 175 | 135 | 0,23 |
| 120 | 11,22 | 456 | 421 | 317 | 231 | 176 | 0,20 |
| 150 | 12,34 | 521 | 462 | 369 | 239 | 181 | 0,16 |
| 200 | 14,21 | 535 | 470 | 393 | 307 | 239 | 0,12 |


alluminio

lato superiore
alluminio 0,6 mm

lato inferiore
alluminio 0,6 mm

| SP | peso | Distanza tra gli appoggi | | | | | U trasmissione |
|-----|-------|--------------------------|------|------|------|------|-------------------|
| | | 1,50 | 2,00 | 2,50 | 3,00 | 3,50 | |
| 25 | 4,46 | 70 | - | - | - | - | 0,98 |
| 30 | 4,64 | 97 | 49 | - | - | - | 0,77 |
| 40 | 4,94 | 155 | 82 | 47 | - | - | 0,58 |
| 50 | 5,33 | 200 | 121 | 71 | 44 | - | 0,46 |
| 60 | 5,79 | 163 | 99 | 62 | 41 | - | 0,38 |
| 80 | 6,47 | 320 | 254 | 160 | 105 | 71 | 0,29 |
| 100 | 7,23 | 400 | 320 | 225 | 154 | 107 | 0,23 |
| 120 | 7,98 | 467 | 398 | 288 | 201 | 146 | 0,20 |
| 150 | 8,82 | 568 | 490 | 330 | 231 | 167 | 0,16 |
| 200 | 10,98 | 602 | 545 | 502 | 301 | 219 | 0,12 |

CARATTERISTICHE TECNICHE



Particolare - Fissaggio a vista